


Pulpmaster 5000 Food Waste Recycling Machine

Features and Benefits

- Fully Stainless Steel for Durability
- Back to Base Communication
- All machine functions monitored
- Liquid cycle for organic liquid waste
- Category 4 Safety Rated
- Low water use average 50L per tonne
- Reduction in waste volume up to 50%

- Auto cycle for quick efficient use
- Tank level monitored electronically
- All mechanical functions in the machine
- Wash cycle for easy cleaning
- Can process 1 kilogram a second
- Power usage average 2.8kwh per tonne
- Reduced Truck Movements







Processes 70 Litres per load in 60 seconds

Machine dimensions

Height 1220 mm (with the lid in the down position) Height 1810 mm (with the lid in the up position) Width 670 mm Depth 680 m Weight 170 kg's

Clearance Dimensions

20mm with the lid up 30mm on the left and right side of the machine 120mm at the rear of the machine



What food waste can go into the Pulpmaster 5000?

Soups

SolidsLiquidsBreadsMilkDairyJuicesEggsGravy

Fruits (including skins) Pan drippings
Legumes Cooling Oil
Meats (including small bones) Yogurt

Pasta Pastries

Poultry (including bones)

Seafood

Vegetables (including skins)

Soft white napkins Corn Starch products

Coffee Grinds



23L Pulpmaster Caddy

Application

The Pulpmaster 5000 batch load version is a stand-alone machine that can easily be located in the commercial kitchen or back of house at many different types of Clients. The Pulpmaster 5000 batch version machine can be 50 meters from the Pulpmaster Tank and has a back to base monitoring system and tank level measuring system. Ideal Market: Fruit & Veg shops, Clubs, Commercial Kitchens, High Schools, Universities Campus Canteens, Large Restaurants and Large Fast Food Outlets.

Pulpmaster Waste Storage Tank – Specifications

2700L Tank Dimensions

Material: HDPE Thickness: 10mm Storage Capacity: 2700 Litres

Height: 1900 mm Length: 2120 mm Width: 1100 mm

Clearance Dimensions – Pulpmaster Tank

Shallow end and wall side - 10 mm

Camlock end – 500 mm Front side – 500 mm Top of tank – 500mm

Features

Rubber seals on the lid and lid frame
One way vent to assist pump outs
Carbon filter for odour control

